



CHASE CORPORATION
Specialty Coatings Group

TAPECOAT / ROYSTON PRODUCT DATA

ENVIROTAPE COLOR COAT

The Multi-Environmental All Purpose Wax Coating System

For Above or Below Grade
UV Resistant
Self Hardening
Wet or Dry Surface Application

Basic Use

Envirotape Color Coat is a multi-environmental coating system, designed to protect piping and metal structures from damage and deterioration caused by corrosion. The specially formulated self-hardening wax coating system is suited for both above and below grade application.

Color Coat is available in Gray, White or Yellow and is resistant to Ultra Violet Light and environmental exposure. The self-hardening outer skin gives this protective coating its durable and aesthetically pleasing quality.

This highly conformable tape coating is ideal for protecting structures such as bridge crossings, riser pipe, flanges, valves, regulator pits and all types of metal piping.

Color Coat conforms well to irregular surfaces and can be applied over most stable surfaces, dry, damp or wet.

Composition

The Color Coat coating system consists of a fully impregnated fiber carrier saturated with a specially formulated blend of waxes and plasticizers, creating this versatile, environmentally safe, easily to apply, protective coating for the widest range of applications.

Technical Data

Colors: Gray, White or Yellow
Other colors available upon request
Thickness: Available in 60 mils and also 40 mils
Maximum Operating Temperature: 140°F

Surface Preparation

Remove all substances that will impede bond, this shall include: all loose surface material, rust, dirt and dust, burrs and sharp edges. Remove excess moisture when possible.

Application

- Primer: Color Coat Enviroprime primer apply a 2 to 4 mil coat to pipe surface.
- Tape: Apply Color Coat using either the spiral or cigarette method.
Recommended Overlap -50%.
Hand smooth and seal overlaps.

Optional Coating Overwrap:

T/R RUGGED WRAP - Fiberglass reinforced outerwrap, UV Resistant, Water Activated. Hand applied with gloves.

Availability:

Standard Rolls: 2", 4" or 6" Wide
Standard Colors: Gray, White, Yellow
Other colors available upon request.

Additional Technical Data and Application Specifications are available from:

THE TAPECOAT COMPANY

P.O. Box 631, Evanston, Illinois 60204-0631, USA
1527 Lyons Street, Evanston, Illinois 60201, USA
Telephone: (847) 866-8500 (800) 758-6041
Fax: (847) 866-8596 (800) 332-8273

www.tapecoat.com

An ISO 9001- 2000 Company revised Jkr08/07

WARRANTY: This product has been designed for use by persons having practical skill and experience in the application of industrial coatings. Before using, user shall determine the suitability of this product for his intended use. Since seller has no control over the specific application of this product, seller's sole warranty with respect to such product is that it is of merchantable quality and meets the quality control standards of The Tapecoat Company. Seller makes no other warranty, express or implied, and seller disclaims all warranties except as set forth herein. Seller shall not be liable under any circumstances for consequential or incidental damages. Seller's liability for breach of warranty hereunder is limited to the purchase quantity of the seller's product proved to be defective.