



CHASE CORPORATION  
CONSTRUCTION PRODUCTS

## TAPECOAT / ROYSTON PRODUCT DATA

### T/R RUGGED WRAP

ABOVE AND BELOW GRADE  
REINFORCED COATING OVERWRAP

UV RESISTANT  
MOISTURE ACTIVATED  
REINFORCED FIBERGLASS MESH  
350°F MAXIMUM OPERATIONAL  
TEMPERATURE

#### Basic Use

T/R Rugged Wrap is a coating overwrap in roll form. Used to strengthen, protect and isolate existing coatings from the detrimental effects of their surrounding environment. Rugged Wrap mesh weave can offer any coating system increased protection from exposure to a wide range of potentially destructive forces such as mechanical damage, abrasion and soil stress both above and below grade. The mesh weave also provides an excellent profile for painting. It can be used to enhance the mechanical strength of all wax coatings systems with operational temperatures ranging from ambient to 350°F and T/R Rugged Wrap will not shield or interfere with cathodic protection systems.

EXCELLENT WAX TAPE  
OVERWRAP

**WARRANTY:** This product has been designed for use by persons having practical skill and experience in the application of industrial coatings. Before using, user shall determine the suitability of this product for his intended use. Since seller has no control over the specific application of this product, seller's sole warranty with respect to such product is that it is of merchantable quality and meets the quality control standards of The Tapecoat Company. Seller makes no other warranty, express or implied, and seller disclaims all warranties except as set forth herein. Seller shall not be liable under any circumstances for consequential or incidental damages. Seller's liability for breach of warranty hereunder is limited to the purchase quantity of the seller's product proved to be defective.

#### Composition

T/R Rugged Wrap is a formulation of plasticizers and resins with a fiberglass mesh carrier that hardens to form a protective overwrap when activated by moisture.

#### Technical Data

Thickness: 30 mils  
Color: SILVER & BLACK  
Other colors available upon request  
Operating Temperature: Ambient to 350°F

#### Application

1. Gloves should be worn during application.
2. Active T/R Rugged Wrap by soaking roll in water for 30 seconds.
3. Squeeze excess water from roll and wrap over existing coating using a 50% overlap. Additional overwraps may be made to achieve desired mechanical strength.

#### Availability:

Rolls: 4" X 10'	10 rolls per case
4" X 20'	10 rolls per case
6" X 30'	5 rolls per case
9" X 50'	1 rolls per case

Additional Technical Data and Application Specifications are available from:

#### THE TAPECOAT COMPANY

P.O. Box 631, Evanston, Illinois 60204-0631, USA  
1527 Lyons Street, Evanston, Illinois 60201, USA  
Telephone: (847) 866-8500 (800) 758-6041  
Fax: (847) 866-8596 (800) 332-8273

[www.tapecoat.com](http://www.tapecoat.com)

An ISO 9001- 2000 Company

Jkrrr08/08